



1019 SE Holbrook Ct.
Port St. Lucie, FL 34952
772-335-8225 - Fax 772-335-3991
DUNS: 00-306-7852

Email: sales@enviroseal.com Web: <http://www.enviroseal.com>

Distributors Worldwide

SIC CODES: 3089 & 5169

DuraSeal Zero™

Zero VOC CONCRETE and MASONRY SEALER

FORMULATED SPECIFICALLY FOR

- ✓ QUARRY TILE
- ✓ MEXICAN & PAVER TILE
- ✓ SLATE
- ✓ FLAGSTONE
- ✓ CONCRETE
- ✓ BRICK
- ✓ TERRAZZO
- ✓ STAMPED CONCRETE

DuraSeal Zero™ is a **Zero VOC** clear acrylic waterborne finish designed to protect and beautify tile, concrete and masonry surfaces. **DuraSeal Zero™** protects against all organic stains including cooking oil, grease and beverages. It may be used indoors or outdoors and is extremely easy to apply and maintain.

USES

- ✓ **Seals, protects and improves appearance of all unglazed tile, stamped and exposed aggregate concrete, brick, natural and manufactured stone, stucco and slate.**
- ✓ **Use to seal concrete and masonry surfaces prior to painting or apply over painted surfaces for added protection and improved appearance.**

FEATURES

- ✓ Repels Oil and Grease Stains
- ✓ Non-Flammable
- ✓ No Harmful Vapors
- ✓ Cleans up with Water
- ✓ Easy to Apply
- ✓ Water Repellent
- ✓ Reduces Efflorescence
- ✓ Can be recoated

PREPARATION

All surfaces must be free of efflorescence, dirt, oil, wax, grease and previously applied paints or sealers. If muriatic acid is used, all acid residue must be removed prior to application.

APPLICATION

Apply one coat of **DuraSeal Zero™** (do not allow it to puddle). A second coat can be applied if surface is very porous. Make sure first coat is dry to the touch before applying second coat; usually one to three hours. Allow **DuraSeal Zero™** additional drying time in moist climates. It can be applied with a brush, roller, or spray-equipment dependent on porosity and roughness of surface. Clean tools with water before sealer dries. Apply between 55° and 90°F. If it is necessary to apply on a warm day in direct sunlight, slightly dampen the surface to be sealed with a fine spray of water prior to application of the sealer. Allow 72 hours curing time against heavy moisture and bulk water. Sealer will continue to gain strength for up to one week.



1019 SE Holbrook Ct.
Port St. Lucie, FL 34952
772-335-8225 - Fax 772-335-3991
DUNS: 00-306-7852

Email: sales@enviroseal.com Web: <http://www.enviroseal.com>

Distributors Worldwide

SIC CODES: 3089 & 5169

COVERAGE

100 to 400 square feet per gallon dependent on porosity of the surface.

PACKAGING

DuraSeal Zero™ is packaged in 5 gallon pails, 55 gallon drums, and 275-gallon totes.

SPECIFICATIONS

BASE Aqueous Acrylic Co-Polymer
DENSITY 8.58 pounds per gallon
SOLIDS +/- 17.5%
APPEARANCE Milky White – Dries Clear.

USES

Seals, protects, and improves appearance of unglazed tile, concrete, brick, natural and manufactured stone, stucco and slate. Can also be used on wood. Use on wood, concrete and masonry surfaces prior to painting.

FEATURES

- | | |
|--------------------------------|-----------------------------|
| ✓ Repels Oil and Grease Stains | ✓ Easy to Apply |
| ✓ Non-Flammable | ✓ Water Repellent |
| ✓ No Harmful Vapors | ✓ Reduces Efflorescence |
| ✓ Cleans up with Water | ✓ Chemical Resistant Finish |

PREPARATION

All surfaces must be free of efflorescence, dirt, oil, wax, grease and defective paint or sealers. If muriatic acid is used, all acid residue must be removed prior to application. Do not allow acid to dry.

COVERAGE

100 to 400 square feet per gallon depending on porosity of the surface.

Important Note: Always test a small area of surface to be sealed to verify penetration and satisfaction of sealed appearance.

Enviroseal Corporation warrants that for a period of 12 months from the date of purchase, Duraseal ZERO™ will be free of manufacturing defects and is warranted to be of uniform quality within tolerances and conforms to published specifications in force on the date. Enviroseal shall only be held liable under this warranty if the material has been stored and used in accordance with published product technical information. Enviroseal has no control over the use of this product and customer agrees to assume full responsibility for each application and Enviroseal assumes no liability for final results. Refer to MSDS and other printed information for additional product details. For professional use only.

Rev-Jan-15